
ergotron®

Zip40 Charging Cart

Includes PowerShuttle™ Technology



Cart dimensions 32.36"W x 44.29"H x 26.15"D (82.2 x 112.5 x 66.4 cm)

Cart weight (without equipment) 175 lb (79 kg)

Rated weight capacity Top Work Surface 25 lb (11.3 kg)

Device Slot Size 17.1"W x 11.2"H (43.4x28.4 cm) Device with case and power cord installed must fit within these dimensions.

Max Dimensions of WAP 10"W x 10"H x 2.2"D (25.4x25.4x5.6 cm)

Cooling/ventilation Four 12V DC fans, ventilated doors and side panel

External power outlet(s) One or two outlets, depending on region 100-120V~, 4A max, 50/60 Hz or 220-240V~, 2A max, 50/60 Hz

WAP and Switch Outlets 100/120V~, 4A max, 50/60 Hz or 220-240V~, 2A max, 50/60 Hz

Amoricas Salos and

insidesales@ergotron.com

Shipping dimensions 37"W x 52"D x 30"H (94x132x75 cm)

Shipping weight 221 lb (100 kg)

Power system 100-120V~,12A, 50/60Hz Maximum input for 5 devices cannot exceed 8.5A or 220-240V~,10A, 50/60Hz Maximum input for 5 devices cannot exceed 4.0A

Environmental Temperature range: Operating 0° to 30°C (32° to 86°F) Storage -40° to 60°C (-40° to 140°F)

Relative humidity (maximum): Operating 10%–90% (non condensing) Storage 5%–95% (non condensing)

Altitude (maximum): 2000 m (6,562 ft)

Certification: UL / IEC 60950 Information Technology Equipment, and UL / IEC 62368 Audio/Video Information and Communication Technology Equipment. CAN/CSA C22.2 No. 60950-1 CAN/CSA C22.2 No. 62368-1 UL 1678 Household, Commercial, and Institutional-Use Carts, Stands, and Entertainment Centers for Use with Audio and/or Video Equipment. ICES-003 Issue 5, Class A FCC Part 15 Class A RoHS and REACH compliant material used.

© 2019 Ergotron, Inc. rev. 02/23/22 DIM-Zip40-2 Content is subject to change without notification

| Corporate Headquarter | EMEA Sales | APAC Sales | Worldwide OEM Sales |
|---|---|---|---|
| St. Paul, MN USA (800) 888-8458 +1-651-681-7600 | Amersfoort, The Netherlands +31 33 45 45 600 www.ergotron.com | Sydney, Australia www.ergotron.com apaccustomerservice@ergotron.com | www.ergotron.com info.oem@ergotron.com |
| www.ergotron.com | info.eu@ergotron.com | | |